

Package: glaredb (via r-universe)

August 15, 2026

Title R Bindings for 'GlareDB'

Version 0.0.5

Description R bindings for 'GlareDB', an analytical database based on 'Apache Arrow' and 'Apache DataFusion' that can connect to various data sources and execute queries.

License AGPL-3

URL <https://eitsupi.github.io/r-glaredb/>,
<https://github.com/eitsupi/r-glaredb>

BugReports <https://github.com/eitsupi/r-glaredb/issues>

Imports nanoarrow

Suggests arrow, knitr, patrick, polars, rlang, rmarkdown, testthat (>= 3.0.0)

Config/glaredb/LibVersion 0.0.4

Config/Needs/dev RcppTOML, devtools, desc, dplyr, fs, gert, glue, lintr, readr, styler, stringr

Config/Needs/website pkgdown

Config/testthat/edition 3

Encoding UTF-8

OS_type unix

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

SystemRequirements Cargo (Rust's package manager), rustc, protobuf-compiler

Config/pak/sysreqs libzstd-dev protobuf-compiler libprotoc-dev libclang-dev

Repository <https://test.r-universe.dev>

Date/Publication 2025-07-21 04:08:48 UTC

RemoteUrl <https://github.com/eitsupi/r-glaredb>

RemoteRef v0.0.5

RemoteSha ff810e8c5a1b7050d84b375b9ef33210102213f0

Contents

as_glaredb_table	2
glaredb_connect	3
glaredb_execute	5
Index	6

as_glaredb_table	<i>Create a GlareDB table</i>
------------------	-------------------------------

Description

GlareDB table is a class that has a struct similar to [arrow::Table](#) innerly and can be converted from/to other classes via [nanoarrow::as_nanoarrow_array_stream\(\)](#).

Usage

```
as_glaredb_table(x, ...)  
  
## Default S3 method:  
as_glaredb_table(x, ..., schema = NULL)  
  
## S3 method for class 'nanoarrow_array_stream'  
as_glaredb_table(x, ...)  
  
## S3 method for class 'RGlareDbExecutionOutput'  
as_glaredb_table(x, ...)
```

Arguments

- x An object to be coerced to a GlareDB table.
- ... Additional arguments passed to methods.
- schema An optional schema used to enforce conversion to a particular type. Defaults to [infer_nanoarrow_schema\(\)](#).

Details

The default method of [as_glaredb_table\(\)](#) calls [nanoarrow::as_nanoarrow_array_stream\(\)](#) internally, and all arguments are passed to it.

Value

A [GlareDB table](#).

Examples

```

con <- glaredb_connect()

# Create a GlareDB table from a data frame with a specified schema
dat <- data.frame(a = 1:3, b = letters[1:3]) |>
  as_glaredb_table(
    schema = nanoarrow::na_struct(
      list(
        a = nanoarrow::na_int64(),
        b = nanoarrow::na_large_string()
      )
    )
  )

# Run an SQL query against the connection,
# and convert the result to a GlareDB table
glaredb_sql("SELECT * FROM dat", con) |>
  as_glaredb_table()

# Convert the GlareDB table to an R data frame
dat |>
  as.data.frame()

# Convert the GlareDB table to an arrow Table
if (requireNamespace("arrow", quietly = TRUE)) {
  dat |>
    arrow::as_arrow_table()
}

# Convert the GlareDB table to a polars DataFrame
if (requireNamespace("polars", quietly = TRUE)) {
  dat |>
    polars::as_polars_df()
}

```

glaredb_connect

*Connect to a GlareDB database***Description**

Connect to a GlareDB database

Usage

```

glaredb_connect(
  data_dir_or_cloud_url = NULL,
  ...,
  spill_path = NULL,
  disable_tls = FALSE,

```

```

cloud_addr = "https://console.glaredb.com",
location = NULL,
storage_options = NULL,
env = parent.frame()
)

```

Arguments

<code>data_dir_or_cloud_url</code>	A character of path to a local GlareDB database or a cloud URL or NULL. If NULL, a in-memory database is used.
<code>...</code>	Ignored.
<code>spill_path</code>	TODO
<code>disable_tls</code>	TRUE or FALSE to indicating whether to disable TLS.
<code>cloud_addr</code>	A character of a GlareDB cloud URL.
<code>location</code>	TODO
<code>storage_options</code>	Named character vector of storage options or NULL (default).
<code>env</code>	The connected environment, an environment class or NULL (means the global env). GlareDB can register some class of R objects inside the environment automatically, so you can access the objects inside this environment by the object name in the query. The default, the caller environment is used.

Value

GlareDB connection object

Examples

```

# Create a connection of in-memory database
con <- glaredb_connect()

# The print result shows the connected environment
con

# The connected environment can be accessed by `$.env`
con$.env

# Create a table to the database and insert data
glaredb_execute("CREATE TABLE my_table (a int)", con)
glaredb_execute("INSERT INTO my_table VALUES (1), (2)", con)

# Query the data and assign the result to a variable
res <- glaredb_sql("SELECT * FROM my_table", con)

# Since the result `res` exists in the connected environment,
# it can be resolved by the object name in the query
exists("res", envir = con$.env)

```

```
glaredb_sql("SELECT * FROM res", con) |>
  as_glaredb_table()
```

glaredb_execute	<i>Run a query against a GlareDB database</i>
-----------------	---

Description

Run a query against a GlareDB database

Usage

```
glaredb_execute(query, connection = NULL)
```

```
glaredb_sql(query, connection = NULL)
```

```
glaredb_prql(query, connection = NULL)
```

Arguments

query	A character of the query to run. - For <code>glaredb_sql()</code> and <code>glaredb_execute()</code>, an SQL query. - For <code>glaredb_prql()</code>, a PRQL query.
connection	A GlareDB connection object or NULL. If NULL, the default in-memory database is used.

Value

A GlareDB execution output (Query plan). For `glaredb_execute()`, the value is returned invisibly.

Examples

```
# You can materialize the query result by `as_glaredb_table()` etc.
glaredb_sql("SELECT 'hello from R' as hello") |>
  as_glaredb_table()
```

```
glaredb_prql("from [
  {a=5, b=false},
  {a=6, b=true},
]") |>
  as.data.frame()
```

```
# `glaredb_execute()` is useful for manipulating the database
glaredb_execute("CREATE TABLE my_table (a int)")
glaredb_execute("INSERT INTO my_table VALUES (1), (2)")
```

```
glaredb_sql("SELECT * FROM my_table") |>
  as_glaredb_table()
```

Index

`arrow::Table`, [2](#)
`as_glaredb_table`, [2](#)
`as_glaredb_table()`, [2](#)

environment class, [4](#)

GlareDB connection object, [5](#)
GlareDB table, [2](#)
`glaredb_connect`, [3](#)
`glaredb_execute`, [5](#)
`glaredb_execute()`, [5](#)
`glaredb_prql` (`glaredb_execute`), [5](#)
`glaredb_prql()`, [5](#)
`glaredb_sql` (`glaredb_execute`), [5](#)
`glaredb_sql()`, [5](#)
`global env`, [4](#)

`infer_nanoarrow_schema()`, [2](#)

`nanoarrow::as_nanoarrow_array_stream()`,
[2](#)

`RGlareDbConnection` (`glaredb_connect`), [3](#)
`RGlareDbTable` (`as_glaredb_table`), [2](#)