

Package: toml (via r-universe)

August 1, 2026

Type Package

Title Read, Write, and Modify TOML Files

Version 1.1.0

Description Simple toolkit for working with TOML text. Based on tomledit which allows for modifying TOML while preserving order, comments, and whitespace.

License MIT + file LICENSE

Encoding UTF-8

Imports jsonlite, V8 (>= 8.0.1)

URL <https://r-lib.r-universe.dev/toml>

BugReports <https://github.com/r-lib/toml/issues>

RoxygenNote 7.3.2

Roxygen list(markdown = TRUE)

Config/pak/sysreqs libssl-dev libnode-dev

Repository <https://test.r-universe.dev>

Date/Publication 2026-06-02 12:04:09 UTC

RemoteUrl <https://github.com/jeroen/toml>

RemoteRef HEAD

RemoteSha b35080382a994e547eef58884241d0aad4192339

Contents

toml	2
Index	3

toml	<i>Parse or Edit TOML text</i>
------	--------------------------------

Description

The `edit_toml()` function modifies values in a TOML text while retaining the order, comments, and whitespace. Use `read_toml()` and `write_toml()` to convert between TOML text and R lists.

Usage

```
read_toml(file, as_json = FALSE)

parse_toml(toml, as_json = FALSE)

write_toml(x, auto_unbox = TRUE)

edit_toml(toml, field, value)
```

Arguments

file	path to file with toml text
as_json	return output as json string instead of R list
toml	string
x	vector or json string to convert to TOML
auto_unbox	convert atomic vectors of length 1 as scalars in TOML, unless they are wrapped in <code>I()</code> . See also jsonlite::toJSON .
field	name of field to change, for example <code>package.version</code> .
value	new value of field to set.

Value

`parse_toml()` returns a list and `edit_toml()` returns the modified TOML text.

References

[toml-edit-js examples](#)

Examples

```
toml <- readLines('https://raw.githubusercontent.com/posit-dev/air/refs/heads/main/Cargo.toml')
toml <- edit_toml(toml, 'workspace.package.rust-version', '1.84')
toml <- edit_toml(toml, 'workspace.dependencies.bla', list(path = "./yolo", rev = "123"))
```

Index

`edit_toml (toml)`, [2](#)
`edit_toml()`, [2](#)
`jsonlite::toJSON`, [2](#)
`parse_toml (toml)`, [2](#)
`read_toml (toml)`, [2](#)
`toml`, [2](#)
`write_toml (toml)`, [2](#)